



HV231-10A High Voltage Probe

Specialty handheld probe

- High voltage probe for AC or DC
- Extended voltage measuring to 40 kV
- Use with standard multimeters with 10 MΩ input impedance

No hassle warranty

No waiting.

No shipping charges.



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive “No Hassle” warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)

General Specifications

| | |
|-----------------------|---|
| Operating Temperature | 0 °C to 50 °C |
| Storage Temperature | - 20 °C to 70 °C |
| Dimensions | 340 mm (13.3 in) Length x 30 mm (1 in) Handle x 75 mm (3 in) Guard |
| Weight | 218 g (7.7 oz) |
| Cable Length | 1 m (39 in) |

Specifications

| Function | Range | Accuracy |
|-------------------------|-------------------------------------|----------|
| Input Resistance | 1000 MΩ | |
| Division Ratio | 1000 : 1 | |
| Maximum Working Voltage | 40 kV DC or AC peak 28 kV AC RMS | |
| Accuracy | | |
| HV231-10A | DC V (1 kV to 20 kV) | ± 1 % |
| | DC V (20 kV to 40 kV) | ± 2 % |
| | AC V (1 kV to 20 kV) (50/60 Hz) | ± 5 % |
| Temperature Coefficient | < 200 ppm/°C | |