



TH-1 Relative Humidity / Temperature Probe Style Meter

Take this small portable RH/Temp meter, Model TH-1 anywhere for those quick comfort-level measurements. Easy to read dual display with Data Hold to freeze measurement result on the screen. Precision capacitive RH sensor with twist-able protective cap.

Compact size goes and measures anywhere

Dual display for RH and Temperature

Also measures Wet Bulb and Dew Point

Put meter into metric or English for measurement results

Stores Min/Max readings for comparisons

Data Hold function

**No hassle
warranty**

No waiting.

**No shipping
charges.**



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)



Specifications

General Specifications	
Sensor	Electronic Capacitance Polymer Film Sensor
Range	Relative Humidity 0 to 100% Temperature -20 to 50°C (-4 to 122°F) DP / WB -20 to 59.9°C / -5 to 59.9°C (-4 to 139.8°F / 23 to 139.8°F)
Accuracy	Relative Humidity ±4%RH from 10 to 95%RH, +5%RH (0 to 10, 95 to 100%RH) @ 25°C (77°F) non-condensing Temperature ±0.6°C (±1°F)
Resolution	0.1%, 0.1°C / 0.1°F
Electrical	
Battery	1 X CR2032 (included)
Battery Life	150 Hours
Power Consumption	<2.0mA
Mechanical	
Size	17.5 x 4.2 x 1.6cm (6.89 x 1.65 x 0.63 in)
Weight	0.052 kg (2 oz.)
Environmental	
Operating Humidity	0 to 100% RH
Operating Temperature	-20 to 50°C (-4 to 122°F)
Storage Temperature	-20 to 50°C (-4 to 122°F)
Agency Approvals & Certifications	
	CE

ACCESSORIES
Carrying Case

