



## WT-30 Salinity Pen-Type Water Quality Meter

Keep the costs and risks of maintaining water quality, distribution and waste under control with these easy to use, one touch water management testers. Allows facility managers to take control of monitoring regulatory compliance and troubleshoot corrosion in building water/waste water systems.

- Measures Salinity from 1.0 to 70.0 ppt (NaCL)
- Dual LCD display with salinity and temperature (selectable C and F)
- Waterproof and dustproof - IP65
- Quick response time
- Easy to calibrate
- Built-in NaCL temperature coefficient
- Built-in NaCL conductivity to TDS conversion factor
- Data hold
- Pen size, easy to fit in pocket
- Low battery indicator
- Auto power-off disable
- Simple one-touch auto-calibration
- Easy One-touch, multi point calibration

### No hassle warranty

*No waiting.*

*No shipping  
charges.*



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)



## WT-30 Salinity Pen-Type Water Quality Meter

## Data Sheet

### Specifications

<b>Salinity Range</b>	0.00 ~ 10.00, 10.1 ~ 70.0 ppt
<b>Resolution</b>	0.01ppt / 0.1ppt
<b>Accuracy</b>	±1% Full Scale ±1 dgt
<b>Normalization</b>	Fixed at 25°C (77°F)
<b>Waterproof Rating</b>	IP 65
<b>Temperature compensation</b>	0°C to 50°C (32°F to 122°F)
<b>Temperature coefficient</b>	Built-in NaCL Temperature coefficient
<b>Operating Temperature</b>	0°C to 50°C (32°F to 122°F)
<b>Power Requirements</b>	4x1.5V batteries (Type A76 or LR44)
<b>Auto Power Off</b>	20 minutes after last key op
<b>Dimension</b>	165 x 35 x 32mm (6.5 x 1.4 x 1.3 in)
<b>Weight</b>	Approx. 56g (0.12 lb)

Contact:  
Industrial Process Measurement, Inc.  
3910 Park Avenue, Unit 7  
Edison, NJ 08820  
732-632-6400  
support@instrumentation2000.com  
<http://www.instrumentation2000.com>

©2009 Amprobe Test Tools. All rights reserved.  
7/2009 3520495 Rev A