



WT-50 Dissolved Oxygen Water Quality Meter

Keep the costs and risks of maintaining water quality, distribution and waste under control with this easy to use, one touch water management tester. Allows facility managers to take control of monitoring regulatory compliance and troubleshoot corrosion in building water/waste water systems.

- Accurate Dissolved Oxygen measurements 0.0 to 199.9% or 0.00 to 19.99ppm
- Dual LCD display with Dissolved Oxygen and temperature (selectable C and F)
- Salinity and barometric pressure compensation
- Built in memory to store and recall 99 measurements together with temperature and time
- Built in USB port to download measurements with optional software and cable
- Ready Indicator prompts whenever reading stabilizes
- Data Hold
- Max/Min/Avg functions help to analyze the data
- Auto-Power off with user selectable time frame
- Low battery indication
- Backlight
- Applications:
 - **Aquaculture** - *To monitor oxygen levels in fish and shrimp farming*
 - **Industrial** - *Ideal for checks the quality of plant water intake and discharge*
 - **Environmental** - *To test water quality, BOD (Biochemical Oxygen Demand) value*
 - **Educational** - *Ideal for quick, accurate Dissolved Oxygen readings in laboratories and schools*

No hassle warranty

No waiting.

*No shipping
charges.*



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)



WT-50 Dissolved Oxygen Water Quality Meter

Data Sheet

Specifications

Dissolved Oxygen %	0.0 ~ 199.9%
RES.	0.1%
Accuracy	±1.5% of F.S
D.O. ppm	0.00 ~ 19.99ppm
RES.	0.01ppm
Accuracy	±1.5% of F.S
Temperature	0°C to 50°C (32°F to 122°F)
RES.	0.1°C (32.2°F)
Accuracy	±0.5°C (± 31.1°F to 32.9°F)
Salinity	0.0 ~ 50.0 ppt
RES.	0.1ppt
Pressure	500 ~ 1499mmHg / L (66.6 ~ 199.9kPA)
RES.	1mmHg / 0.1kPA
Memory	99 point
Real Time	Yes
Dimension	175 x 70 x 33 mm (6.9 x 2.8 x 1.3 in)
Weight	Approx. 157g (0.35 lb)
Package Contains	Meter, Battery, Instruction manual, Carrying pouch, Probe, pH standard solution, Syringe, Membrane, O-ring

Contact:
Industrial Process Measurement, Inc.
3910 Park Avenue, Unit 7
Edison, NJ 08820
732-632-6400
support@instrumentation2000.com
<http://www.instrumentation2000.com>

©2009 Amprobe Test Tools. All rights reserved.
77/2009 3520513 Rev A