

Fruit Hardness Tester

 **Penetrometer measures fruit ripeness**
to improve fruit quality, harvest, storage, and product transportation time

Features:

- Four Penetrometer tips for large/hard and small/soft fruits
- Basic accuracy of 0.5%
- Tension or Compression, Peak hold and Zero functions
- Positive/Reverse display for easy readability
- Large LCD with back light feature
- RS-232 PC interface
- Optional software available (407001)
- Complete with four (3mm, 5mm, 8mm,11mm) Penetrometer Tips, six AA 1.5V batteries, and hard carrying case



Complete with four (3mm, 5mm, 8mm,11mm) Penetrometer Tips, six AA 1.5V batteries, and hard carrying case

Specifications	
Range	44.10lbs, 20kg, 196.10 Newtons
Accuracy	±(0.5% + 2 digits)
Resolution:	0.01 lbs, 0.01 kg, 0.05 Newtons
Minimum Display	0.07 lbs, 0.02kg, 0.3 Newtons
Display:	5 digits, 0.63" (16mm) LCD display
Update Rate:	Fast mode 0.2 secs, Slow mode 0.6 secs.
Full scale deflection:	approx 0.4mm
Transducer type:	Load cell
Peak Hold:	Freezes Max reading on display
Power Supply:	Six 1.5V AA batteries
Weight:	1.4 lbs (650g)
Size:	8.5 x 3.5 x 1.8" (215 x 90 x 45mm)

Ordering Information:

FHT200Fruit Hardness Tester
407001Data Acquisition program and cable
407001-USBUSB adaptor for 407001
153117117V AC adaptor
UA100-240100 to 240VAC adaptor with 3 plugs (US, EU, UK)

Contact:
Industrial Process Measurement, Inc.
3910 Park Avenue, Unit 7
Edison, NJ 08820
732-632-6400
support@instrumentation2000.com
<http://www.instrumentation2000.com>

