



**Model 5677B  
Deluxe Multi-Use DMM Maxi-Test Lead Kit**




MODEL 5907A  
FLEXIBLE TEST LEAD SET WITH RIGHT ANGLE AND STRAIGHT BANANA PLUGS  
QTY 2 : 1 RED, 1 BLACK




MODEL 6041B  
EXTRA LARGE ALLIGATOR CLIP SET  
QTY 2 : 1 RED, 1 BLACK



MODEL 6252  
TEST LEAD COUPLER SET  
QTY 2 : 1 RED, 1 BLACK




MODEL 5953A  
RETRACTABLE TIP TEST PROBE SET  
QTY 2 : 1 RED, 1 BLACK



MODEL 6153  
SPADE LUG ADAPTER SET  
QTY 2



MODEL 5246  
IC TEST PROBE TIP ADAPTER SET  
QTY 2 : 1 RED, 1 BLACK




MODEL 6248  
MINIGRABBER TEST CLIP WITH DMM JACK SET  
QTY 2 : 1 RED, 1 BLACK



MODEL 6364  
0.080 REPLACEMENT PROBE TIP SET  
QTY 1: SET




MODEL 5689A  
REPLACEMENT MODULAR TEST PROBE SET  
QTY 2 : 1 RED, 1 BLACK



MODEL 6261  
MINIPINCER TEST CLIP WITH DMM JACK SET  
QTY 2 : 1 RED, 1 BLACK



MODEL 5916A  
MEDIUM ALLIGATOR CLIP SET  
QTY 2 : 1 RED, 1 BLACK



FOUR-FOLD NYLON POUCH

**FEATURES:**

- Test leads with a right angle banana plug are ideal for use with hand held digital multimeter.
- Flexible test leads feature high strand count silicone wire for extreme flexibility and high temperature resistance.
- Wear indication with double insulated (dual extruded) silicone leads shows white inner layer for increased safety.
- Banana plugs are molded directly to the wire for superior pull strength.
- Retractable needle tip test probe, allowing easy access of hard to reach test points.
- Probes, alligator clips and spade lugs fit directly onto test leads for test versatility.
- Interchangeable test probe tips allows for test versatility from general purpose to SMD applications.
- Test accessories conveniently store in the four-fold nylon pouch.
- Compatible with most multimeters that accept safety style sheath banana plugs.
- CE Compliant; complies with IEC 61010-031 standard for hand held accessories.

Contact:  
Industrial Process Measurement, Inc.  
3910 Park Avenue, Unit 7  
Edison, NJ 08820  
732-632-6400  
support@instrumentation2000.com  
http://www.instrumentation2000.com

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.